



ITEM	SELECTABLE CONTENTS
DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN
POLARIZER TYPE	REFLECTIVE TRANSMISSIVE TRANSMISSIVE, POSITIVE TRANSMISSIVE, NEGATIVE
VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK WHITE Y-G RED GREEN AMBER TRI-COLOR
LED BACKLIGHT	STANDARD TEMPERATURE WIDE TEMPERATURE
TEMPERATURE RANGE	-
CHARACTER PATTERNS	- - -
OPERATING VOLTAGE	3.3V
LED DRIVING VOLTAGE	4.5V
LED DRIVE METHOD	1/16DUTY, 1/5BIAS
LED DRIVE IC	ST7032I COG

NOTE:

1	2	3	4	5	6	7	8
THE PART NUMBER IN MASS PRODUCTION							
1.-Y-G STN, TRANSMISSIVE LCD; Y-G BACKLIGHT; 6 O'CLOCK							
2.-							
3.-							
4.-							
5.-							
6.-							
1							
2							
3							
4							
5							
6							
7							
8							

UNIT	TOLERANCE
MM	X.X = ±0.2
3RD ANGLE	X.XX = ±0.10
ANG	= -

SCALE: 1:1

DRAWN: _____

CHECKED: _____

APPROVED: _____

TITLE: LCM

MODEL NO: AQM0802A SERIES

PART NO: _____

REV A

SH NO 1/1

DISPLAYTRONIC

XIAMEN ZETTLER ELECTRONICS CO., LTD.