



-	BL-
+	BL+
14	DB7
13	DB6
12	DB5
11	DB4
10	DB3
9	DB2
8	DB1
7	DB0
6	E
5	RVW
4	RS
3	VO
2	VDD
1	VSS
PIN	SYMBOL



ITEM	T1	T2
BACKLIGHT	8.6	13.5
WITHOUT TBL	4.6	9.5



ITEM	SELECTABLE CONTENTS
DISPLAY MODE	STN YELLOW MODE
	STN GRAY MODE
	STN BLUE MODE
	FSTN
POLARIZER TYPE	REFLECTIVE
	TRANSPARENT
	TRANSMISSIVE_POSITIVE
	TRANSMISSIVE_NEGATIVE
VIEWING DIRECTION	6 O'CLOCK
	12 O'CLOCK
LED BACKLIGHT	WHITE
	Y-G
	RED
	GREEN
	BLUE
	AMBER
	TRI-COLOR
TEMPERATURE RANGE	STANDARD TEMPERATURE
	WIDE TEMPERATURE
CHARACTER PATTERNS	ENGLISH-JAPANESE FONTS
	ENGLISH-EUROPEAN FONTS
	ENGLISH-RUSSIAN FONTS
	CYRILLIC FONTS
	HEBREW FONTS
OPERATING VOLTAGE	5V
LCD DRIVING VOLTAGE	4.5V
LCD DRIVE METHOD	1/16 DUTY 1/5 BIAS
LCD DRIVE IC	ST7068U

**NOTE:**

- 1.The backlight can be driven by pin +, pin - or pin1, pin2 which is selectable.
- 2.The voltage of backlight is depended on the backlight color and the value of current-limiting resistance.
- 3.The operating voltage can be driven by 3.3v which is selectable.

**THE PART NUMBER IN MASS PRODUCTION**

- 1.GRAY OR Y-G STN, TRANSPARENT LCD; Y-G BACKLIGHT; 6 O'CLOCK OR 12 O'CLOCK;
- 2.FSTN, TRANSPARENT LCD; BLUE OR WHITE BACKLIGHT; 6 O'CLOCK OR 12 O'CLOCK;
- 3.Y-G STN, TRANSPARENT LCD; WHITE BACKLIGHT; 6 O'CLOCK;
- 4.Y-G STN, TRANSMISSIVE LCD; Y-G BACKLIGHT; 6 O'CLOCK;
- 5.BLUE STN, TRANSMISSIVE NEGATIVE LCD; WHITE BACKLIGHT; 6 O'CLOCK OR 12 O'CLOCK;
- 6.GRAY OR Y-G STN, REFLECTIVE LCD; WITHOUT BACKLIGHT; 6 O'CLOCK OR 12 O'CLOCK;

UNIT	MM	TOLERANCE
		X.X = ±0.3
		X.XX = ±0.20
		AND = ±
3RD ANGLE		
SCALE:	1:1	
DRAWN:		
CHECKED:		
APPROVED:		

**ZETTLER DISPLAYS**

XIAMEN ZETTLER ELECTRONICS CO., LTD.

TITLE:	LCM		
MODEL NO:	ACM1602K SERIES	REV	A
PART NO:		SH NO	1/1